



EXCEL+™

HEAVY-DUTY ANTI-SEIZE



EXCEL+™ is a copper-based anti-seize lubricant formulated to withstand high temperatures and extreme pressures. Continues ground conductivity better than ordinary lubricants. Seals out moisture, gases and corrosive fluids from threaded connections. Copper-Moly combination prevents seizing, galling and premature wear. Contains rust and corrosion inhibitors to assure long life of connectors.

(716) 597-0214

www.wellworthproducts.com

DIRECTIONS:

1. SHAKE CAN VIGOROUSLY FOR ONE MINUTE.
2. Clean surface thoroughly. Apply only enough to form a solid film over contact surfaces of threads, gaskets, bushings, etc.
3. Assemble and wipe off excess.
4. INVERT CAN AFTER EACH USE AND SPRAY A SHORT BURST TO CLEAR VALVE.

Product Number and Packaging:
#3020 – 12/CS

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

For more information, refer to the Well Worth Safety Data Sheet for this product, or call ChemTrec (USA) 800-424-9300

KEEP OUT OF REACH OF CHILDREN

WARNING: Cancer and Reproductive Harm.
www.P65Warnin.gs.c.a.g.ov

PRECAUTIONS: Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other pressurized container. Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear eye protection. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated place.

CONTAINS: n-Butane [106-97-8], Acetone [67-64-1], Propane [74-98-6], Heptane [142-82-5], Distillates, hydrotreated light. [64742-47-8].

FIRST AID:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
IF SWALLOWED: Immediately call a poison center or doctor. DO NOT induce vomiting.

STORAGE AND DISPOSAL: Protect from sunlight. Do not expose to temperatures exceeding 50° C/122°F. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state and federal regulations.